



Polyimide-Filled Polytetrafluoroethylene (SP191)

Material Data Sheet
M-64 (Rev. 01; 04-9-18)

19650 Pauling
Foothill Ranch, CA
USA 92610-2610
t +1 949 460 2100
f +1 949 460 2300

Jollemanhof 16, 5th floor
1019 GW Amsterdam
The Netherlands
t +31 20 638 6523
f +31 20 625 6018

Suite 901, Chinachem
Century Tower
178 Gloucester Road,
Wanchai, Hong Kong
t +852 28681860
f +852 22956753

www.balseal.com



Overview

SP191 is a polyimide-filled PTFE compound which exhibits low friction and minimal wear in rotary and reciprocating sealing applications. SP191 performs well against soft mating surfaces such as aluminum, mild steel, brass, and plastics, and it is ideal for use in stop-start applications where the goal is to eliminate stick-slip. This material is suggested for use in applications with service temperatures ranging from -400 °F to 550 °F (-240 °C to 287 °C).

Chemical Compatibility

SP191 exhibits excellent compatibility with most fluids and gases. For more details, reference Technical Report 60A, "Chemical Compatibility Guide," in the technical library section of our website at www.balseal.com.

FDA Compliance

SP191 is a composition which contains ingredients that meet FDA regulation 21 CFR 170.39 for use in food contact applications. Bal Seal Engineering defines its compositions as "FDA Compliant" if each of the ingredients in the composition have been found by the FDA to be "safe for use in food contact" or "acceptable for use in food contact."

Color

Tan (color variations may occur during processing)

Mechanical Properties of SP191

Tensile Strength (typical)	Elongation (typical)
2800 psi (19 MPa)	225%

Advantages

- Low friction
- Extremely low wear
- Increased hardness
- Broad useful temperature range of -400 °F to 550 °F (-240 °C to 287 °C)

Application Examples

- Industrial robotics (assembly, food processing)
- Low pressure HPLC pumps
- Surgical tools
- Aerospace gimbals/pods/pan-tilt systems

Other Information

For more information, contact a technical sales representative, or e-mail us at sales@balseal.com.

It is essential that the customer run evaluation testing under actual service conditions with a sufficient safety factor to determine if the proposed, supplied or purchased Bal Seal Engineering, Inc. products are suitable for the intended purpose and to confirm expected results. Bal Seal Engineering, Inc. shall not be liable for any loss or damage of any kind or nature that may result from the use of, reference to, or reliance on the information contained herein, including but not limited to consequential, special (including loss of profits) direct, indirect, incidental or similar damages, even if Bal Seal Engineering, Inc. has been advised of the possibility of such damages. Products contained herein may be covered by all or in part by one or more of the following U.S. Patents: 8,054,459. Products contained herein may be covered all or in part by various pending U.S. Patents.

©Copyright 2018 Bal Seal Engineering, Inc. U.S.A.