


EXTRUSION LENGTHS OF BAL SEAL® MATERIALS USED IN HIGH-PRESSURE SERVICE

Seals used in plunger pumps are often subject to pressures as high as 30,000 psi (2,109 kg/cm²). These seals are subject to extrusion, depending on the temperatures, pressures and radial clearances.

Listed below are the extrusion values of various Bal Seal® materials tested at pressures from 10,000 to 30,000 psi (703 to 2,109 kg/cm²). The testing method for Bal Seal UPC-16 and GFP-10 materials is shown in Figure 1A. The testing method for Bal Seal P-41 material is shown in Figure 1B. Test results are shown in Table 1.



Method Used to Test Extrusion of Bal Seal Materials

Material	Pressure PSI (kg/cm ²)	"E" Clearance Inch (mm)	"L" Extrusion Inch (mm)	Pressure PSI (kg/cm ²)	"E" Clearance Inch (mm)	"L" Extrusion Inch (mm)
UPC-16	10,000 (703)	0.004 (0.10) 0.010 (0.25) 0.018 (0.46)	0.0017 (0.043) 0.0028 (0.071) 0.0038 (0.097)	15,000 (1,055)	0.004 (0.10) 0.010 (0.25)	0.0079 (0.201) 0.0100 (0.254)
				30,000 (2,109)		0.0194 (0.493)
GFP-10	10,000 (703)	0.004 (0.10) 0.010 (0.25) 0.018 (0.46)	0.0037 (0.094) 0.0058 (0.147) 0.0068 (0.173)	20,000 (1,406)	0.004 (0.10) 0.010 (0.25)	0.0110 (0.279) 0.0257 (0.653)
P-41	30,000 (2,109)	0.004 (0.10) 0.010 (0.25) 0.018 (0.46)	Not measurable 0.0006 (0.015) 0.0011 (0.028)	UPC-16: Ultra-high molecular weight polyethylene GFP-10: Graphite-fiber reinforced PTFE High-performance BAL™ Seal aromatic polymer P-41:		

FIGURE 2:
Extrusion of Bal Seal seals and back-up rings when pressure is sustained for sixty minutes at 70°F (21°C) at the pressures and radial clearances indicated

Extrusion increases as pressure and radial clearance ("E") increases. Bal Seal P-41 material has the greatest extrusion resistance. No measurable extrusion was recorded at 30,000 psi (2,109 kg/cm²) or at a radial clearance of 0.004 inch (0.10 millimeter). Optimum results are obtained when the seal is supported with a P-41 back-up ring and radial clearances are minimized.

For more information and technical assistance, consult the Technical Sales Department.

PATENTS: The items described in this page include products that are the subject of issued United States and foreign patents or products where patents are pending, including the following: Patents 6,641,141 B2; 7,210,398 B2; 6,161,838; 5,992,856; 5,134,244

U.S. Address: 19650 Pauling Foothill Ranch, CA 92610-2610 • Phone: (949) 460-2100 • Fax: (949) 460-2300
 BV Address: Jollemanhof 16, • 1019 GW Amsterdam • The Netherlands • Phone: 31 20 638 65 23 • Fax: 31 20 625 60 18

Rev.D 10-16-07 (11-276)

Bal Seal Engineering, Inc. is certified to ISO 9001 | www.balseal.com